

# State of the Practice of Onsite Leachate Treatment at Municipal Solid Waste Landfills

James Wally, PE

Pradeep Jain PhD, PE

Tim Townsend PhD, PE



# Leachate Quantity

- 
- 16 billion gallons of MSW leachate annually in the US<sup>1</sup>
  - Average leachate collection rate<sup>2</sup>
    - 108 GPAD in areas with annual precipitation amounts of 56 inches per year
    - 22 GPAD in areas with annual precipitation amounts of 22 inches per year



# Leachate Management Strategies

- Treatment at a WWTP via force main or tanker truck
  - Historically the most common and cheapest strategy
  - Often cooperation between biosolids and leachate management
  - If landfill and WWTP are public entities, in some cases, no money may change hands
- Treatment Onsite
  - May be pre-treatment before discharging onsite
  - May treat and discharge or otherwise manage onsite
    - Evaporation, infiltration, recirculation, or surface water discharge
- Other Management Strategies
  - E.g. Evaporation, deep well injection, recirculation



# The Leachate Problem

- Increasingly, WWTPs are unable to accept raw leachate.
- Many landfill operators are exploring onsite treatment or pretreatment.
- Leachate represents one of the largest ongoing costs for operation and post-closure care<sup>2</sup>
  - Leachate is still generated for up to 22 years after installation of a final cover system



# Leachate Quality

- Leachate treatment limiting parameters
  - Ammonia
  - Organic compounds (may be measured as COD, BOD, color, or TOC)
  - TDS
- Trace metals and organic chemicals are present at but typically do not require additional treatment to specifically target.
  - Some sites may have specific concerns such as arsenic.
  - Emerging contaminants such as PFAS may become a limiting factor in the future<sup>1</sup>
- Leachate changes over the life of the landfill. Typically,
  - Ammonia and TDS concentrations increase<sup>2</sup>
  - Organics decrease, but those that remain are resistant to biological degradation<sup>2</sup>



# Wastewater Chemistry of MSW Landfill Leachate

Constituent	Range (mg/L)	
	Leachate <sup>3</sup>	
Total Solids*	2,000-60,000	
BOD <sub>5</sub>	20-57,000	
TOC	30-29,000	
COD	140-152,000	
Organic-N	14-2,500	
Ammonia-N	50-2,200	
Total Phosphorous	0.1-23	
Chloride	150-4,500	
Sulfate	8-7,750	
Alkalinity	610-7,320	

3. Kjeldsen et al., 2002

\*Sources did not distinguish between dissolved and suspended solids. Generally, leachate is dominated by the former

# Wastewater Chemistry of Domestic Wastewater vs MSW Landfill Leachate

Constituent	Range (mg/L)	
	Leachate <sup>3</sup>	Domestic Wastewater <sup>4</sup>
<b>Total Solids*</b>	2,000-60,000	300-1,200
<b>BOD<sub>5</sub></b>	20-57,000	100-400
<b>TOC</b>	30-29,000	100-400
<b>COD</b>	140-152,000	200-1,000
<b>Organic-N</b>	14-2,500	4-40
<b>Ammonia-N</b>	50-2,200	10-50
<b>Total Phosphorous</b>	0.1-23	5-20
<b>Chloride</b>	150-4,500	30-85
<b>Sulfate</b>	8-7,750	20-60
<b>Alkalinity</b>	610-7,320	50-200

3. Kjeldsen et al., 2002

4. Burks and Minnis, 1994

\*Sources did not distinguish between dissolved and suspended solids. Generally, leachate is dominated by the former

# Onsite Leachate Treatment – State of the Practice


- 
- Onsite leachate management strategies are diverse
  - Selection of a management strategy is dictated by
    - Climate
    - Economics
    - Regulation
    - Leachate characteristics
    - Site characteristics





# ITS Leachate Database


- Over 500 landfill sites included
- Compiled from publicly available data
- Not a representative survey
- Not comprehensive






# Economic and regulatory factors

- Factors other than climate are evident in the database
- Differences can be driven by
  - Economic factors
  - Regulatory factors




# Disposal Strategy Prevalence

- Out of 527 sites:
- 297 sites rely on onsite treatment (rather than offsite disposal after pre-treatment or no treatment)




# Onsite Leachate Management Strategies (ITS Leachate Database)



# Biological Treatment Technologies

- Aeration is most common, often pretreatment
  - Floating or submerged aerators
- Sequential Batch Reactor (SBR) and Activated Sludge the dominant biological treatment-to-discharge method.
  - These are similar to a traditional WWTP
- Phytoremediation, wetland, and MBR are relatively uncommon.
  - Some of these may be considered “emerging technologies”
  - Proprietary data and confidentiality hampered data collection on these technologies
  - No wetland site was identified for an active MSW landfill



# Biological Treatment Technologies


---

- Advantages

- Can reduce ammonia and BOD
- Some technologies may reduce total solids via dilution


- Challenges:

- High ammonia loading may damage biological processes
- BOD removal will reduce as the landfill ages
- No solids reduction mechanism except dilution
- May have larger footprint and/or require intensive operation
- Used as a pretreatment or with a discharge strategy



# Evaporation Treatment Technologies


- Climatic Evaporation
  - Open pond leachate storage in arid climates
- Thermal Evaporation
  - Combustion of landfill gas, natural gas,
  - Use of electric heat
- Mechanical Evaporation
  - Increase the surface area of leachate
  - Air misting systems
  - Fabric systems which drip leachate through a elevated fabric
  - Proprietary data and confidentiality hampered data collection on these technologies






# Evaporation Treatment Technologies

- Thermal Evaporation
  - Combustion of landfill gas, natural gas,
  - Use of electric heat
  - Can be configured to reduce or eliminate VOC emissions
- Mechanical Evaporation
  - Increase the surface area of leachate
  - Air misting systems
  - Fabric systems which drip leachate through a elevated fabric
  - Proprietary data and confidentiality hampered data collection on these technologies




# Disposal Management Methods

- Recirculation
  - Injection of leachate into vertical or horizontal wells
  - Spraying directly onto the active working face of the landfill
  - Infiltration ponds or trenches over lined footprint
- Land Application
  - sprayed with fixed sprinklers, mobile sprinklers, or water trucks over a fixed area
  - Requires pretreatment
- Deep Well Injection
  - Treated leachate is pump directly into a deep aquifer




# Physico-chemical Treatment Technologies


- Many of these technologies are part of a treatment train:
  - Clarifier, Activated Carbon, Media filter, Airstripper, UV, Chemical, precipitation, coagulation, and/or oxidation
  - Complex treatment trains tended to be older sites
- Reverse Osmosis (RO) and other membrane processes (UF, NF, or MF) occurred in isolation and with pretreatment
- Processes are either pretreatment, or paired with a discharge strategy



# Onsite Leachate Management Strategies and Treatment Technologies (ITS Leachate Database)



# Onsite Leachate Management Strategies and Treatment Technologies (FL Sites - ITS Leachate Database, 2019)



# Case Studies

6 case studies were selected to represent the range of geographies and strategies

Site Name	Site location (state)	Treatment / Management Category	Technology	Disposal Method
Site A	North Carolina	Physiochemical	Reverse Osmosis	Surfacewater
Site B	Florida	Biological	SBR	Sprayfield
Site C	North Carolina	Evaporation	Thermal Evaporator	
Site E	Florida	Physicochemical	Aeration and filtration	Sprayfield
Site D	Texas	Biological	Phytoremediation	
Site F	Arizona	Evaporation	Climatic Evaporation	

# Membrane Treatment Case Study – RO

- 
- Landfill is located in North Carolina and was constructed in 1981
  - Leachate collection has ranged from 20,000 GPD to 120,000 GPD
  - In 2001, the site began operation of a 5-acre wetland treatment system
    - Effluent was discharged to a local river
    - Discontinued in 2016 as effluent failed to meet discharge criteria for heavy metals
  - In 2016, the site began operation of a RO treatment system
    - Treatment capacity of 65,000 GPD
    - Permeate (75-85% of effluent) is discharged to a local river
    - Concentrate (15-25% of effluent) is spray-irrigated on the working face or recirculated
    - RO membranes have not required replacement in the three years of operation

# Membrane Treatment Case Study – RO


- In 2016, the site began operation of a RO treatment system
  - Treatment capacity of 65,000 GPD
  - Permeate (75-85% of effluent) is discharged to a local river
  - Concentrate (15-25% of effluent) is spray-irrigated on the working face or recirculated
  - RO membranes have not required replacement in the three years of operation
- State requires operator on-site during operation
- Site meets very strict surface water discharge criteria
  - Arsenic treated to non-detect
  - Recent study found removal of PFAS to non-detect
- Operators are highly satisfied with the system






# RO Cost Data

- Cost highly variable. Large factors include:
  - Complexity of pretreatment
  - Requirements for onsite operator
- Capital costs varied from \$50,000 to \$3 million



# Biological Treatment Case Study – SBR

- Landfill is located in Florida and was constructed in 1969
- Leachate collection has ranged 6 to 11 million gallons per year
- Prior to 2010, leachate was treated by evaporation via a spray system, recirculated, or disposed of at a WWTP
- In 2010, the site began operation of a SBR system
  - Treatment capacity of 90,000 GPD
  - Sludge is dewatered and disposed of in the landfill




# Biological Treatment Case Study – SBR

- 
- Effluent discharged to a 26-acre sprayfield
  - Monitored via groundwater wells surrounding sprayfield
  - Challenges
    - Elevated ammonia frequently disrupts the system and requires re-inoculation
    - Site struggles to meet solids standards
    - Recent consultant recommendation is to add RO as a post-treatment step.
  - Capital cost was \$4.4 million (2010 dollars)
  - Operating costs unavailable




# Thermal Leachate Evaporation Case Study

- Landfill is located in North Carolina
- Leachate collection ranged from 28 to 37 million gallons per year
- Prior to 2013, leachate was recirculated and disposed of at a WWTP
- In 2013, the site began operation of an LFG fueled thermal evaporator
  - Treatment capacity of 34,000 GPD
  - Water vapor is discharged to the atmosphere after passing through the enclosed flare for VOC destruction
  - Evaporation residues are disposed of in the landfill or hauled offsite for disposal
  - System is comprised of an evaporator tank and a clarifier tank
  - Vapor discharge limits include ammonia, arsenic and chromium



# Phytoremediation Case Study

- Landfill is located in Texas and began receiving waste in 2004
- Leachate collection data was limited but 2.8 million were reported for 2011
- Prior to 2017, leachate was disposed of at a WWTP
- In 2017, the site began operation of a phytoremediation system
  - Treatment capacity of 12,000 GPD
  - Uses vetiver grass over 4.7 acres of treatment footprint
  - Utilizes a drip irrigation system
- No data on performance or cost



# Physico-Chemical Case Study

- 
- Landfill is located in Florida and began receiving waste in 1996
  - Since waste accepting operations began leachate has been recirculated or treated
  - physico-chemical system
    - Two sand media filters and a chemical addition disinfection system
    - The leachate is then disinfection with chlorine




# Physico-Chemical Case Study

- 
- Treated leachate is land-applied via a sprayfield.
  - The ultimate monitoring point is a set of groundwater monitoring wells
    - This allows for phytoutilization and attenuation to contribute to treatment.
    - Site has been operating successfully since 1994 with no exceedances
    - Large sprayfield and site footprint allows space for attenuation




# Physico-Chemical Case Study

## Capital Costs – 2019 dollars





# Physico-Chemical Case Study




# Climatic Evaporation Case Study

- Landfill is located in Arizona and began receiving waste in 1993
- 144 acres of landfill waste disposal area
- 400 to 500 thousand gallons per year
- Precipitation around 7 inches per year
- All leachate collected at Site F is either evaporated or recirculated
- Leachate is stored in a 0.7-acre pond, which is open to the air
- Sludge from the pond is removed every 5 to 10 years when enough has accumulated



# Climatic Evaporation Case Study


- Significant recirculation of leachate to accelerate waste degradation
- Between 200,000 and 1.2 million gallons per year recirculated.



# Summary

- 
- Selection is highly site-specific, and should include
    - Climate
    - Economics
    - Regulation
    - Leachate characteristics
    - Site characteristics
  - Confidentiality has made assessing the state of the practice challenging.
  - Some technologies appear to be unable to meet contemporary treatment needs such as
    - complex treatment trains
    - some biological processes
  - Some technologies appear to be filling those gaps:
    - Membrane
    - Evaporation

# Estimated costs<sup>5,6</sup>





Questions

# References

1. Lang, J.R., Allred, B.M., Field, J.A., Levis, J.W., and Barlaz, M.A. (2017). National Estimate of Per- and Polyfluoroalkyl Substances (PFAS) Release to U.S. Municipal Landfill Leachate. *Environmental Science & Technology*. 51(4). 2197-2205.
2. Tolaymat, T., Krause, M., and Carson, D. (2020). Technical Considerations for Evaluating the Environmental Emissions from RCRA Subtitle D Landfills Beyond the 30-Year Post-Closure Care Period. U.S. Environmental Protection Agency, Washington, DC, EPA/600/R-20/346, 2020.
3. Kjeldsen, P., Barlaz, M.A., Rooker, A.P., Baun, A., Ledin, A., and Christensen, T.H. (2002). Present and Long-term Composition of MSW Landfill Leachate: A Review. *Critical Reviews in Environmental Science and Technology*, 32 (4), 297-336.
4. Burks, B.D. and Minnis. M.M. (1994). Onsite Wastewater Treatment Systems. Madison, WI: Hogarth House, Ltd.
5. SWANA (2014). Onsite Treatment of Landfill Leachate. A Report Prepared by the Solid Waste Association of North America Applied Research Foundation 2014 Disposal Group Subscribers
6. Brown and Cooper (2013). Treatment Methods for Leachate Impacted by Landfill gas Well Pumping. 2013 South Carolina Solid Waste Associate of North America Spring Conference.